

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

We Protect Hoosiers and Our Environment.

100 N. Senate Avenue • Indianapolis, IN 46204 (800) 451-6027 • (317) 232-8603 • www.idem.IN.gov

Eric J. Holcomb

Bruno L. Pigott

July 12, 2019

Mr. Matt Gluckman Watersheds Section Chief, Water Division U.S. Environmental Protection Agency R5, W-15J 77 West Jackson Boulevard Chicago, IL 60604-3507

Dear Mr. Gluckman:

The Deep River—Portage Burns Watershed Total Maximum Daily Load (TMDL) report was submitted by the Indiana Department of Environmental Management (IDEM) to the U.S. Environmental Protection Agency (U.S. EPA) and approved by the U.S. EPA on September 26, 2014. Subsequent to its approval, inaccuracies in the final report were discovered by IDEM, who informed U.S. EPA in December 2017. IDEM explained that it had mischaracterized how bacteria TMDLs in the final Deep River—Portage Burns Watershed TMDL report describes that bacteria loadings were calculated based on the *E. coli* water quality standard of 125 cfu/100 mL as a geometric mean. However, the actual loading calculations for the TMDLs were based on a single sample maximum water quality standard of 235 cfu/100 mL. These misstatements were limited to the main body of the report only, and do not impact any bacteria TMDL calculations.

IDEM has identified portions of the final report which are subject to the above referenced errors and made the necessary revisions. References and revisions are provided as an attachment to this letter.

Please direct any questions or comments to Angela Brown at 317-308-3102.

Sincerely,

Angela Brown

Chief, Watershed Planning and Restoration Section

Office of Water Quality

Ungela M Ba

Cc: David Werbach, U.S. EPA Region 5 Paul Proto U.S. EPA Region 5



Deep River-Portage Burns Watershed Final TMDL Report Revisions

References with accompanying language revisions to the inaccuracies included in the final Deep River-Portage Burns TMDL report approved by U.S. EPA on September 26, 2014 are listed as follows:

-Section 2.2.1

Original Document Language:

The target value used for the Deep River-Portage Burns Watershed TMDL was based on the 125 counts/100 mL geometric mean component of the standard (i.e., daily loading capacities were calculated by multiplying flows by 125 counts/100 mL). This approach ensures that both components of the standard will be met since a daily loading capacity based on 125 counts/100 mL will, by definition, meet the 235 counts/100 mL component of the standard. The use of the geometric mean component of the standard results in an added margin of safety (see Section 8.2 for more details).

Revised Document Language:

The Deep River-Portage Burns TMDL *E. coli* target is: from April 1 through October 31, *E. coli* shall not exceed 235 cfu/100 mL. For *E. coli* TMDLs, allocations were calculated based upon the 235 cfu/100 mL portion of the criteria. U.S. EPA believes this target value is protective of both portions of the criteria. The U.S. EPA report, "An Approach for Using Load Duration Curves in the Development of TMDLs" (U.S. EPA, 2007) describes how the monthly geometric mean (in this case, 125 cfu/100 mL for *E. coli*) is likely to be met when the single sample maximum value (in this case, 235 cfu/100 mL for *E. coli*) is used to develop the loading capacity. The process calculates the daily maximum bacteria value that is possible to observe and still attain the monthly geometric mean. If the single sample maximum is set as a never-to-be surpassed value then it becomes the maximum value that can be observed, and all other bacteria values would have to be less than the maximum, i.e., 235 cfu/100 mL. U.S. EPA notes that whichever portion of the criteria is used to determine the allocations, both the monthly geometric mean and single sample maximum will be used to assess the extent of implementation by point and nonpoint sources.

-Section 5.0 (Table 31)

Target value in original table:

No value should exceed 125 counts/100 mL (geometric mean)

Target value in revised table:

No value should exceed 235 cfu/100 mL

-Section 8.1

Original Document Language:

The WWTPs are estimated to contribute to the phosphorus load in the Deep River-Portage Burns. The WWTP TMDL loadings were established based on the design flow multiplied by the TMDL target value for bacteria: 125#/100 mL for *E. coli*, for TP: 0.3 mg/L and for TSS: 30 mg/L. These loadings are then incorporated into the NPDES permitted facility. The *E. coli* limitations are directly into the permit.

Revised Document Language:

The WWTPs are estimated to contribute to the phosphorus load in the Deep River-Portage Burns. The WWTP TMDL loadings were established based on the design flow multiplied by the TMDL target value for bacteria: 235 cfu/100 mL for *E. coli*, for TP: 0.3 mg/L and for TSS: 30 mg/L. These loadings are then incorporated into the NPDES permitted facility. The *E. coli* limitations are directly into the permit.

Section 8.2

Original Document Language:

- The *E. coli* TMDLs include an implicit MOS in that they were based on the geometric mean component of the standard rather than the single sample maximum standard. Using the single sample maximum standard would have resulted in larger loading capacities.
- An additional implicit MOS for E. coli is included because the load duration analysis does not address die-off of pathogens.

Revised Document Language:

• An additional implicit MOS for *E. coli* is included because the load duration analysis does not address die-off of pathogens. As stated in *EPA's Protocol for Developing Pathogen TMDLs* (EPA 841-R-00-002), many different factors affect the survival of pathogens, including the physical condition of the water. These factors include, but are not limited to sunlight, temperature, salinity, and nutrient deficiencies. These factors vary depending upon the environmental condition/circumstances of the water, and therefore it would be difficult to assert that the rate of decay caused by any given combination of these environmental variables was sufficient enough to meet the water quality standards of 235 cfu/100mL and 125 cfu/100 mL. Thus, it is more conservative to apply the State's water quality standard in determining bacteria TMDLs, because this standard must be met at all times under all environmental conditions.

Section 9.2

Original E. coli Goal Statement:

The AUIDs in the Deep River-Portage Burns watershed should meet the 125 counts/100 mL (geometric mean) TMDL target value.

Revised E. coli Goal Statement:

The AUIDs in the Deep River-Portage Burns watershed should meet the 235 cfu/100 mL TMDL target value.

			<i>i</i>	